



Führungsbüchsen Hartmetall Canon

Serge Meister

Type	Canon typ A / B / Inter / Tournant							Alésage min.			Alésage max.		
	No. Art.	Fournisseurs / Supplier		dimension extérieur / outside				φ min. / min. bore			φ max. / max. bore		
	Art. Nr.	Hersteller / Proveedor		Aussen Masse / medida de fuera				min. Bohrung / taladro min.			max. Bohrung / taladro max.		
	Meister Swiss	Neukomm	Dünner	φ	L	M	β	d min.	6pans	carré	d max.	6pans	carré
B	600	51.001 / 200		7.0	29.0	6 x 0.5	30°	0.31	1.0	1.0	4.0	3.5	2.5
I	1601	50.001	J 2	7.0	30.0	6 x 0.5	16°	0.31	1.0	1.0	3.5	3.0	2.5
A	451	2.001	1002	9.0	30.0		19°	0.31	1.0	1.0	4.0	3.5	2.5
B	351	150	B201	9.0	50.0	8 x 0.6	30°	0.31	1.0	1.0	5.0	4.5	2.5
B	600S	60.001	B242	9.0	26.0	6 x 0.5	30°	0.31	1.0	1.0	4.5	4.0	3.0
I	1351	51.001 / 200	J 3	9.0	44.0	8 x 0.75	16°	0.31	1.0	1.0	5.0	4.5	3.0
A	453	6.001	1004	11.0	30.0		19°	0.50	1.0	1.0	6.5	5.5	4.5
B	352	5.001		11.0	50.0	10 X 0.6	30°	0.50	1.0	1.0	7.5	6.0	4.0
I	1352	3.001 / 203	J 4	11.0	53.0	10 X 0.8	16°	0.50	1.0	1.0	7.5	6.0	5.0
B	103		B211	12.0	50.0	12 X 1.0	30°	0.50	1.0	1.5	8.0	6.5	5.5
I	1603	53.001	J 5	12.0	50.0	10 X 0.75	16°	0.50	1.0	1.5	7.5	6.0	5.0
T	3400T	113.001 / 10	B300	13.0	41.5	12.5X0.75	15°	0.70	1.0	1.5	8.0	7.0	5.0
T	3300T	207 / 50	B304	14.0	64.0	13 X 0.75	16°	0.70	1.0	1.5	8.0	7.0	5.5
A	203	104.001	1024	16.0	40.0	30°	30°	0.70	1.0	1.5	8.0	7.0	5.5
A	457	9.001	1008	16.0	30.0		19°	0.70	1.5	1.5	10.0	8.0	7.0
B	603		B203	16.0	61.0	15 X 1.0	30°	0.70	1.5	1.5	11.0	9.5	8.0
I	1353	8.001 / 206	J 6 R	16.0	59.0	14 X 1.0	16°	0.70	1.5	1.5	10.5	9.0	7.5
I	1604	54.001 / 103	J 6	16.0	59.0	14 X 1.0	16°	0.70	1.5	1.5	10.5	9.0	7.5
B	353			17.0	61.0	15 X 1.0	30°	1.00	1.5	2.0	12.0	10.0	8.0
B	853	166.001 / 208	B212A	18.0	59.0	16 X 1.0	30°	1.00	1.5	2.0	13.0	11.0	9.0
T	Top 100			18.0	100.0	18 X 1.0	20°	1.00	1.5	3.0	13.0	11.0	9.0
A	204	105.001	1025	20.0	40.0	30°	30°	1.00		2.0	11.0	9.0	7.5
B	104		B208	20.0	55.0	20 X 1.0	30°	1.00	1.5	2.0	13.0	11.0	9.0
T	221T	450.001 / 800	B301	21.0	57.5	18 X 1.0	12°	1.50	2.0	2.0	11.0	9.5	8.0
I	1354	13.001	J 7 A	22.0	68.0	19 X 1.0	16°	1.50	2.0	2.0	16.0	14.0	11.0
T	39001T	39.001	J 7 AR	22.0	68.0	22 X 1.0	16°	1.50	2.0	2.0	18.0	15.0	13.0
A	459	15.001	1010	24.0	42.0		19°	1.50	2.0	2.0	15.0	13.0	10.0
B	605	61.002 / 106	B238	24.0	61.0	24 X 1.0	30°	1.50	2.0	2.0	16.0	14.0	11.0
B	354		B213	25.0	63.0	25 X 1.0	30°	2.00	2.0	3.0	18.0	15.0	13.0
T	3402T	13	B302	27.0	57.5	24 X 1.0	12°	2.00	2.5	3.0	16.0	14.0	11.0
A	460	16.001	1011	28.0	45.0		29°	2.00	2.5	3.0	20.0	17.0	14.0
I	1357	18.001	B260	28.0	81.0	25 X 1.0	30°	2.00	2.5	3.0	21.0	18.0	15.0
T	223T	22.001	B261	28.0	82.0	25 X 1.0	16°	2.00	2.5	3.0	21.0	18.0	15.0
A	205	107.001	1026	30.0	60.0	29°	29°	2.50	2.5	3.0	17.0	14.0	12.0
A	461	17.001	1012	32.0	45.0		19°	2.50	3.0	3.0	22.0	19.0	15.0
B	355	110	B214	32.0	71.0	32 X 1.0	30°	2.50	2.5	3.0	22.0	19.0	15.0
A	206	108.001	1027	34.0	60.0	29°	29°	2.50	3.0	3.0	22.0	19.0	15.0
T	227T	451.001 / 227	B227	34.0	87.5	34 X 1.0	10°	2.50	3.0	4.0	25.0	22.0	18.0
T	Top 200	Top 200		34.0	150.0	32 X 1.5	20°	3.00	3.0	4.0	26.0	22.0	18.0
A	462	20.001	1013	38.0	45.0		19°	3.00	3.0	4.0	28.0	24.0	19.0
A	463	21.001	1030	38.0	60.0		19°	3.00	3.0	4.0	28.0	24.0	19.0
B	105	61.001	B207	40.0	71.0	40 X 1.0	30°	3.00	3.0	4.0	30.0	26.0	20.0
B	854	172.001	B207 A	40.0	72.0	36 X 1.0	30°	3.00	4.0	4.0	26.0	22.0	20.0
A	207	110.001	1028	42.0	72.0	29°	29°	3.00	4.0	4.0	26.0	22.0	20.0
A	465	29.001	1032	42.0	60.0		19°	3.00	4.0	4.0	28.0	24.0	20.0
T	229T	28.001 / 229	J 9	42.0	82.0	40 X 1.0	16°	4.00	4.0	4.0	32.0	26.0	20.0
I	1355	27.001	J 10	44.0	87.0	40 X 1.0	20°	4.00	4.0	4.0	32.0	26.0	20.0
A	464	30.001	1031	46.0	60.0		19°	4.00	4.0	4.0	32.0	26.0	20.0
A	208	111.001	1029	48.0	72.0	29°	29°	4.00	4.0	4.0	28.0	26.0	18.0

Für grössere Mengen und für andere Ausführungen kontaktieren Sie bitte unseren Verkauf

Tel: +41 61 935 93 00, verkauf@fabry.ch, www.fabry.ch